



SAFETY DATA SHEET B7455

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name B7455
Container size 200ml, 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator.

1.3. Details of the supplier of the safety data sheet

Supplier Bondloc UK Ltd
Units 1 & 2 Bewdley Business Park
Long Bank
Bewdley
Worcestershire
DY12 2TZ
United Kingdom
+44 (0)1299 269269
+44 (0)1299 269210
sales@bondloc.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1299 269269

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229
Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

B7455

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Contains propan-2-ol

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

propan-2-ol	60-100%
CAS number: 67-63-0	EC number: 200-661-7
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
N,N-dimethyl-p-toluidine	<1%
CAS number: 99-97-8	EC number: 202-805-4
Classification	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT RE 2 - H373	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	Move affected person to fresh air at once.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Do not induce vomiting. Rinse mouth. Move affected person to fresh air at once. Get medical attention if any discomfort continues.

B7455

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation May cause respiratory system irritation. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Skin contact May cause irritation. Prolonged skin contact may cause redness and irritation.

Eye contact May irritate eyes. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Carbon oxides and other toxic gases or vapours Extremely flammable. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products Irritating gases or vapours. Toxic gases or vapours. Highly flammable gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Use water spray to reduce vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions Provide adequate ventilation. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

B7455

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with inert, damp, non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Eliminate all sources of ignition. Provide adequate ventilation.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

Advice on general occupational hygiene Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Flammable/combustible materials. Do not store near heat sources or expose to high temperatures. Keep container tightly closed, in a cool, well ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear protective clothing.

Hygiene measures

Provide eyewash station. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

B7455**SECTION 9: Physical and Chemical Properties****9.1. Information on basic physical and chemical properties**

Appearance	Aerosol.
Colour	Clear.
Odour	Characteristic.
Odour threshold	No information available.
pH	Not applicable.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	< -40°C
Evaporation rate	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8% Upper flammable/explosive limit: 9.5%
Vapour pressure	Not applicable.
Vapour density	No information available.
Solubility(ies)	Not applicable.
Partition coefficient	Not available.
Auto-ignition temperature	440-580°C
Decomposition Temperature	No information available.
Viscosity	<1 cps @ 25°C
Explosive properties	No information available.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 603.3 g/l.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity Exothermic reaction with: cyanoacrylates

10.2. Chemical stability

Stability Highly volatile

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight. Do not pierce or burn, even after use.

10.5. Incompatible materials

Materials to avoid Keep away from flammable and combustible materials. No specific material or group of materials is likely to react with the product to produce a hazardous situation.

B7455**10.6. Hazardous decomposition products**

Hazardous decomposition products Heating may generate the following products: Carbon dioxide (CO₂). Carbon monoxide (CO). Other toxic gases and vapours

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity - oral**

ATE oral (mg/kg) 20,000.0

Acute toxicity - dermal

ATE dermal (mg/kg) 60,000.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 600.0

Reproductive toxicity

Reproductive toxicity - fertility May damage fertility.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Inhalation of vapour or mist may cause lung oedema. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

Ingestion

Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact

Irritating to skin. Prolonged or repeated exposure may cause severe irritation.

Eye contact

Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards

Narcotic effect.

Route of exposure

Inhalation Skin absorption

Target organs

Central nervous system Respiratory system, lungs

SECTION 12: Ecological Information**Ecotoxicity**

The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity**Ecotoxicity****12.2. Persistence and degradability**

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient

Not available.

12.4. Mobility in soil

B7455

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water and will spread on the water surface. The product contains volatile substances which may spread in the atmosphere.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Do not puncture or incinerate, even when empty.

SECTION 14: Transport information**14.1. UN number**

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels**14.4. Packing group****14.5. Environmental hazards**

B7455**Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Dangerous Preparations Directive 1999/45/EC.
-----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories**EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

SECTION 16: Other information

Revision date	03/10/2014
SDS number	4637
Hazard statements in full	H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H301 Toxic if swallowed. H311 Toxic in contact with skin. H319 Causes serious eye irritation. H331 Toxic if inhaled. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

WARRANTY: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.