



Technical data Sheet

REV 00 of 20.10.2012

NATURAQUA TOP GEL

For Interiors/Exteriors

DESCRIPTION:

NATURAQUA TOP GEL is a waterborne not foiling finish, based on natural waxes and resins. It penetrates deeply into the wood, enhances the grain while highlighting the structure, and gives a soft satin sheen finish. The precious substances which is made with, combined with UV filters, prevent the formation of chromophore molds and the attack of wood-eater insects, while providing excellent resistance to weather.

CHEMICAL/PHYSICAL CHARACTERISTICS:

Form:	liquid
Colour:	pursuant to labeling
Odour:	odourless
Viscosity:	40" (Cup Ford n°4)
Dry weight:	27%
Viscosity of implementation:	ready to use
Cleaning of tools:	water

METHOD OF USE:

Ready to use, it is recommended to apply it by brush (always the first coat), on clean and dry supports. On external support apply at least two coats, the second one after a minimum of 8 hours from the first. The complete drying is obtained after 24 hours. If necessary lightly sand the support before the application of the second coat.

For particularly cured finishes, after application by brush, it is recommended to use a cloth.



BORMA WACHS[®]

Wood Professional Cosmetics

STORAGE:

Store in a cool, well ventilated place, keep the container closed when not in use. Keep away from heat, flames, sparks and other sources of ignition.

Keep from freezing.

PACKAGING:

The product comes in 375 mL, 750 mL, 2.5 Lt cans.

WARNING:

Our technical sheets are compiled on the bases of results of our tests. Nevertheless our technical advice is given in good faith, but without a guarantee. Indeed different supports, conditions, applications, installations, dilutions are integrating parts of the final result and often beyond every control. The user must test the supplied products to verify if it is adaptable for his/her needs.

We can guarantee the continuity of the physical and chemical characteristics.